



Home > Equipment > Bale Processors > BPX9000 > Compare Models

Dimensions and Weights

	BPX9000
Length	15' (4.6 m)
Height	8.5' (2.6 m)
Width - Transport	8.2' (2.5 m)
Width - Operation	11.2' (3.4 m)
Weight	5060 lbs (2295.2 kg)
Drawbar Weight	1460 lbs (662.2 kg)

Tractor Requirements

	BPX9000
Horsepower Required	85 hp (63.4 kw)
Horsepower maximum	Not applicable hp (kw)
PTO speed	1000 rpm
Hydraulics type	3- Double Acting
Hydraulic Pressure	2000 psi (137.9 bar)
Hydraulic flow rate	8 gpm (30.3 L/min)

Standard Details

	BPX9000
Axle adjustment	Not applicable
Bale rotation	3 Roller Chains with Bolt-On Cross Slat
Bale size capacity	Two Bales, 6' x 5'
Bale weight capacity	2500 lbs (1134 kg)
Blower	Not applicable
Cut Control Bar Adjustment	Not applicable
Cut Control Bar Quantity	Not applicable
Discharge Direction	Right Hand

Standard Details	
	BPX9000
Flail description	7/16" x 5 9/16" tempered spring
Flail Drum Diameter	26.8" (67.9 cm)
Flail Drum Length	78" (198.1 cm)
Flail Drum Speed	1000 rpm
Flail Quantity	30
Hitch Jack	5000 lb. (2267.96kg)
Horizontal spread distance	Not applicable' (m)
Safety Chain Kit	Not applicable
Spout Length	Not applicable' (m)
Spout Deflector	Not applicable
Spout Rotation	Not applicable
Tire Size - Standard	14L x 16.1FL
Torque Protection - Driveline	Shear bolt

Optional Features	
	BPX9000
Extra Cut Control Bars Kit	Not applicable
Flotation Tires	16.5L- 16.1SL 6 SOFTRAC II
Hydraulic Cut Control Bar Kit	Not applicable
Square bale kit	Yes

Copyright © 2010-2015. Vermeer Corporation. All Rights Reserved.

www.vermeer.com